



Rexus RS residential

Χρώμα: Blue

Υλικό: resins and fiberglass

Περιγραφή

Made of fiberglass and acid resistant resins internally, are extremely reliable even under seriously adverse conditions.

Top lid diameter 214mm with air relief and pressure meter.

Thick walls permit working pressure up to 2,5 bars with dimensional stability.

2" inlet-outlet, bottom collector arms with 0,2mm slots.

Filtration depth of 450mm.

Filtration volumes given below refer to filtration loading of 50m/hr (m3/m2/hr).

6-way multiport valve and filtering media not included.

ΤΕΧΝΙΚΕΣ ΠΡΟΔΙΑΓΡΑΦΕΣ

P20102: RS 460, 8,2m3/hr, Ø460 x 820mm, 1 1/2" weight of filtering media: 85kg suggested

Premier-L pumps: P10104, P10108

P20104: RS 610, 14,5m3/hr, Ø610 x 870mm, 1 1/2" weight of filtering media: 175kg suggested

Premier-L pumps: P10106, P10109

P20106: RS 760, 22,6m3/hr, Ø760 x 1010mm, 2" weight of filtering media: 300kg suggested

Premier-L pumps: P10107, P10110

P20108: RS 920, 33,0m3/hr, Ø920 x 1120mm, 2" weight of filtering media: 400kg suggested

Premier-L pumps: P10111