



## Tubular heat exchangers

**Χρώμα:** Silver

### Περιγραφή



Tubular, spiral heat exchangers for pool heating from central heating system. Made entirely of stainless steel AISI 316 corrosion resistant (eg chlorine).

Maximum operating pressure 10 bar.

Possibility of parallel connection of more than one alternator for larger capacity pools.

### ΤΕΧΝΙΚΕΣ ΠΡΟΔΙΑΓΡΑΦΕΣ

- P70100:** 35,000 kcal / hour, power 40kW. Suitable for swimming pools with a capacity of 30 - 40m<sup>3</sup>  
Boiler water inlet / outlet: 3/4 " Pool water inlet / outlet: 1 1/2 "
- P70102:** 65,000 kcal / hour, power 75kW. Suitable for swimming pools with a capacity of 60 - 70m<sup>3</sup>  
Boiler water inlet / outlet: 1 " Pool water inlet / outlet: 1 1/2 "
- P70104:** 93,000 kcal / hour, power 105kW. Suitable for swimming pools with a capacity of 90 - 100m<sup>3</sup>  
Boiler water inlet / outlet: 1 " Pool water inlet / outlet: 2 "
- P70106:** 122,000 kcal / hour, power 140kW. Suitable for swimming pools with a capacity of 120 - 130m<sup>3</sup>  
Boiler water inlet / outlet: 1 " Pool water inlet / outlet: 2 "
- P70108:** 182,000 kcal / hour, power 209kW. Suitable for swimming pools with a capacity of 180 - 190m<sup>3</sup>  
Boiler water inlet / outlet: 1 " Pool water inlet / outlet: 2 "