

Premier 555

Color: Gold

Material: plastic from NORYL

Description

The **new series** of the famous Premier pumps. Casing in thermoplastic, Noryl (**type N**) or fiber glass filled polypropylene (**type P**). Impeller and all other parts in Noryl. Transparent lid, large prefilter easily accessible, single and three phase motor, IE3 efficiency class (European norms) with internal heat protection switch, stainless steel shaft, sunction - discharge Φ63 or 2" female. The pump may retrofit some other makes of pumps.

TECHNICAL SPECIFICATIONS

Single phase pump - N type	
555N-050-1	0,36 KW (0,50HP), 230V, 7,4m3/hr
555N-075-1	0,50 KW (0,75HP), 230V, 11,6m3/hr
555N-100-1	0,75 KW (1,0HP), 230V, 15,3m3/hr
555N-150-1	1,1 KW (1,5HP), 230V, 21,6m3/hr
555N-200-1	1,5 KW (2,0HP), 230V, 26,0m3/hr
Three phase pump - N type	
555N-075-3	0,50 KW (0,75HP), 380V, 11,6m3/hr
555N-100-3	0,75 KW (1,0HP), 380V, 15,3m3/hr
555N-150-3	1,1 KW (1,5HP), 380V, 21,6m3/hr
555N-200-3	1,5 KW (2,0HP), 380V, 26,0m3/hr
555N-300-3	2,2 KW (3,0HP), 380V, 32,0m3/hr

Single phase pump - P type	
555P-050-1	0,36 KW (0,50HP), 230V, 7,4m3/hr
555P-075-1	0,50 KW (0,75HP), 230V, 11,6m3/hr
555P-100-1	0,75 KW (1,0HP), 230V, 15,3m3/hr
555P-150-1	1,1 KW (1,5HP), 230V, 21,6m3/hr
555P-200-1	1,5 KW (2,0HP), 230V, 26,0m3/hr
Three phase pump - P type	
555P-075-3	0,50 KW (0,75HP), 380V, 11,6m3/hr
555P-100-3	0,75 KW (1,0HP), 380V, 15,3m3/hr
555P-150-3	1,1 KW (1,5HP), 380V, 21,6m3/hr
555P-200-3	1,5 KW (2,0HP), 380V, 26,0m3/hr
555P-300-3	2,2 KW (3,0HP), 380V, 32,0m3/hr