



Premier 555

Χρώμα: Gold

Υλικό: plastic from NORYL



Περιγραφή

The **new series** of the famous Premier pumps. Casing in thermoplastic, Noryl (**type N**) or fiber glass filled polypropylene (**type P**). Impeller and all other parts in Noryl. Transparent lid, large prefilter easily accessible, single and three phase motor, IE3 efficiency class (European norms) with internal heat protection switch, stainless steel shaft, suction - discharge $\Phi 63$ or 2" female. The pump may retrofit some other makes of pumps.

ΤΕΧΝΙΚΕΣ ΠΡΟΔΙΑΓΡΑΦΕΣ

555N-050-1:	0,36 KW (0,50HP), 230V, 7,4m ³ /hr
555N-075-1:	0,50 KW (0,75HP), 230V, 11,6m ³ /hr
555N-100-1:	0,75 KW (1,0HP), 230V, 15,3m ³ /hr
555N-150-1:	1,1 KW (1,5HP), 230V, 21,6m ³ /hr
555N-200-1:	1,5 KW (2,0HP), 230V, 26,0m ³ /hr
555N-075-3:	0,50 KW (0,75HP), 380V, 11,6m ³ /hr
555N-100-3:	0,75 KW (1,0HP), 380V, 15,3m ³ /hr
555N-150-3:	1,1 KW (1,5HP), 380V, 21,6m ³ /hr
555N-200-3:	1,5 KW (2,0HP), 380V, 26,0m ³ /hr
555N-300-3:	2,2 KW (3,0HP), 380V, 32,0m ³ /hr
555P-050-1:	0,36 KW (0,50HP), 230V, 7,4m ³ /hr
555P-075-1:	0,50 KW (0,75HP), 230V, 11,6m ³ /hr
555P-100-1:	0,75 KW (1,0HP), 230V, 15,3m ³ /hr
555P-150-1:	1,1 KW (1,5HP), 230V, 21,6m ³ /hr
555P-200-1:	1,5 KW (2,0HP), 230V, 26,0m ³ /hr
555P-075-3:	0,50 KW (0,75HP), 380V, 11,6m ³ /hr
555P-100-3:	0,75 KW (1,0HP), 380V, 15,3m ³ /hr
555P-150-3:	1,1 KW (1,5HP), 380V, 21,6m ³ /hr
555P-200-3:	1,5 KW (2,0HP), 380V, 26,0m ³ /hr
555P-300-3:	2,2 KW (3,0HP), 380V, 32,0m ³ /hr